

01 Specs 02 Title	Connection cable 12V AC / 15,0 m /01		29.11.16 AO VS.02	Project No.
Item / No.	Description / Quantity / Unit		Unit Price	Total
01.1 Position	<p>Description: Connection cable for the connection of products with 12V AC</p> <p>Suitable for dry and wet assembly.</p> <p>Environmental conditions for dry application: none</p> <p>Environmental conditions for wet application (waterquality): Installation and operation in fresh-, pool- and seawater.*</p> <p>Technical data: Length: 15,0m Cable (H07RN-F): 2 x 2,5 mm² Patented reliable plug: yes Integrated water barrier: yes</p> <p>*</p>			
water-quality-matrix				
		Freshwater	Poolwater	Seawater
PH.Value	7,2 -7,6		7,2 -7,6	
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3		8 -15 ° DH; 142 -267 ppm CaCo3	
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal		0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal		< 200 mg/l; < 24,2 moz/gal	
Salinity	n. d.		n. d.	
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal		< 250mg/l; < 30,28 moz/gal	
Temperature	4 -35° C; 39 - 95 ° F		4 -30° C; 39 - 86 ° F	
Supply and delivery according to manufacturer specifications.				
Product / proof of delivery:				
Connection cable 12V AC / 15,0 m /01 Art. 11740				
OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800				
(or equivalent)				
.....				
Entered by the bidder				