

01 Specs 02 Title	Connection cable 12V AC / 1,0 m /01			29.11.16 AO VS.02	Project No.
Item / No.	Description / Quantity / Unit			Unit Price	Total
01.1 Position	<p><b>Description:</b>  <b>Connection cable for the connection of products with 12V AC</b></p> <p>Suitable for dry and wet assembly.</p> <p><b>Environmental conditions for dry application:</b>  none</p> <p><b>Environmental conditions for wet application (waterquality):</b>  Installation and operation in fresh-, pool- and seawater*.</p> <p><b>Technical data:</b>  Length: 1,0m  Cable (H07RN-F): 2 x 2,5 mm<sup>2</sup>  Patented reliable plug: yes  Integrated water barrier: yes</p> <p>*</p>				
<b>water-quality-matrix</b>					
		<b>Freshwater</b>	<b>Poolwater</b>	<b>Seawater</b>	
PH.Value	7,2 -7,6		7,2 -7,6		8
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3		8 -15 ° DH; 142 -267 ppm CaCo3		20 -30 ° DH; 356 - 534 ppm CaCo3
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal		0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal		< 0,3 mg/l; < 0,036 moz/gal
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal		< 200 mg/l; < 24,2 moz/gal		<=22000 mg/l; <=2664 moz/gal
Salinity	n. d.		n. d.		<= 4%; <= 40.000 ppm
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal		< 50 mg/l; < 6,06 moz/gal		< 250mg/l; < 30,28 moz/gal
Temperature	4 -35° C; 39 - 95 ° F		4 -30° C; 39 - 86 ° F		4 - 20 ° C; 39 - 68 ° F
Supply and delivery according to manufacturer specifications.					
Product / proof of delivery:					
<b>Connection cable 12V AC / 1,0 m /01 Art. 12768</b>					
OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800					
(or equivalent)					
.....					
Entered by the bidder					