

01 Specs 01Title	Comet 10 - 12 Silver	01.09.16 AO VS.02	Project No.
Item / No.	Text / Menge / Einheit	Unit price	Total price
01.1 Position	<p>Description: Clear stream nozzle made of chromed and nickel plated brass.</p> <p>Installation and operation in freshwater.*</p> <p>Technical data: Dimensions (Ø x H): 47,3 x 118 [mm] Material: double coated brass Weight: 0,45 kg Effect height: 0,5 - 8,0 [m] Nozzle diameter at orifice: 12 mm Adjustable angular range: 15° Water-level independent: yes</p> <p>Double nipple: Material: double coated brass Integrated flow rectifier: yes Connecting thread (Outside thread): G1</p> <p>Union nut: Material: double coated brass Chamfered: yes Connecting thread (Inner thread): G1 Wrench size: AF41</p> <p>*</p>		
water-quality-matrix			
	Freshwater	Poolwater	Seawater
PH.Value	7,2 -7,6	7,2 -7,6	8
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F
<p>Supply and delivery according to manufacturer specifications.</p> <p>Product / proof of delivery: Comet 10 - 12 Silver Art. 45454</p> <p>OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800</p> <p>(or equivalent)</p> <p>..... Entered by the bidder</p>			