

01 Specs 01Title	Comet 10 - 14 Silver			01.09.16 AO VS.02	Project No.																																				
Item / No.	Description / Quantity / Unit			Unit price	Total price																																				
01.1 Position	<p>Description: Clear stream nozzle made of chromed and nickel plated brass.</p> <p>Installation and operation in freshwater.*</p> <p>Technical data: Dimensions (Ø x H): 47 x 118 [mm] Material: double coated brass Weight: 0,45 kg Effect height: 0,5 - 10,0 [m] Nozzle diameter at orifice: 14 mm Adjustable angular range: 15° Water-level independent: yes</p> <p>Double nipple: Material: double coated brass Integrated flow rectifier: yes Connecting thread (Outside thread): G1</p> <p>Union nut: Material: double coated brass Chamfered: yes Connecting thread (Inner thread): G1 Wrench size: AF41</p> <p>*</p> <table border="1" data-bbox="300 1108 1214 1608"> <thead> <tr> <th colspan="4" data-bbox="300 1108 1214 1137">water-quality-matrix</th> </tr> <tr> <th data-bbox="300 1137 459 1167"></th> <th data-bbox="459 1137 719 1167">Freshwater</th> <th data-bbox="719 1137 979 1167">Poolwater</th> <th data-bbox="979 1137 1214 1167">Seawater</th> </tr> </thead> <tbody> <tr> <td data-bbox="300 1167 459 1234">PH.Value</td> <td data-bbox="459 1167 719 1234">7,2 -7,6</td> <td data-bbox="719 1167 979 1234">7,2 -7,6</td> <td data-bbox="979 1167 1214 1234">8</td> </tr> <tr> <td data-bbox="300 1234 459 1301">Hardness</td> <td data-bbox="459 1234 719 1301">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="719 1234 979 1301">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="979 1234 1214 1301">20 -30 ° DH; 356 - 534 ppm CaCo3</td> </tr> <tr> <td data-bbox="300 1301 459 1357">Free Chlorine</td> <td data-bbox="459 1301 719 1357">< 0,3 mg/l; < 0,036 moz/gal</td> <td data-bbox="719 1301 979 1357">0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td> <td data-bbox="979 1301 1214 1357">< 0,3 mg/l; < 0,036 moz/gal</td> </tr> <tr> <td data-bbox="300 1357 459 1413">Chlorine concentration</td> <td data-bbox="459 1357 719 1413">< 250 mg/l; < 30,28 moz/gal</td> <td data-bbox="719 1357 979 1413">< 200 mg/l; < 24,2 moz/gal</td> <td data-bbox="979 1357 1214 1413"><=22000 mg/l; <=2664 moz/gal</td> </tr> <tr> <td data-bbox="300 1413 459 1480">Salinity</td> <td data-bbox="459 1413 719 1480">n. d.</td> <td data-bbox="719 1413 979 1480">n. d.</td> <td data-bbox="979 1413 1214 1480"><= 4%; <= 40.000 ppm</td> </tr> <tr> <td data-bbox="300 1480 459 1536">Total Dry Residue</td> <td data-bbox="459 1480 719 1536">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="719 1480 979 1536">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="979 1480 1214 1536">< 250mg/l; < 30,28 moz/gal</td> </tr> <tr> <td data-bbox="300 1536 459 1608">Temperature</td> <td data-bbox="459 1536 719 1608">4 -35° C; 39 - 95 ° F</td> <td data-bbox="719 1536 979 1608">4 -30° C; 39 - 86 ° F</td> <td data-bbox="979 1536 1214 1608">4 - 20 ° C; 39 - 68 ° F</td> </tr> </tbody> </table>			water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																									
	Freshwater	Poolwater	Seawater																																						
PH.Value	7,2 -7,6	7,2 -7,6	8																																						
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																						
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																						
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																						
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																						
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																						
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																						
<p>Supply and delivery according to manufacturer specifications.</p> <p>Product / proof of delivery: Comet 10 - 14 Silver Art. 50723</p> <p>OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800</p> <p>(or equivalent) Entered by the bidder</p>																																									