

01 Specs 01Title	Schaumsprudler 75 - 20 silver			05.09.16 KF VS.03	Project No.
Item / No.	Description / Quantity / Unit			Unit Price	Total
01.1 Position	<p>Description: Water-level independent stainless steel nozzle to create a homogenous and stable foam/frothy jet.</p> <p>Installation and operation in freshwater.*</p> <p>Technical data: Dimensions (Ø x H): 100 x 240 [mm] Material: double coated brass Weight: 4,3 kg Connecting thread (Outside thread): G2 Effect height: 0,25-10 [m] Nozzle orifice diameter: approx. 75 mm Integrated flow rectifier: yes Water-level independent: yes</p> <p>*</p>				
water-quality-matrix					
		Freshwater	Poolwater	Seawater	
PH.Value	7,2 -7,6		7,2 -7,6		8
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3		8 -15 ° DH; 142 -267 ppm CaCo3		20 -30 ° DH; 356 - 534 ppm CaCo3
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal		0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal		< 0,3 mg/l; < 0,036 moz/gal
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal		< 200 mg/l; < 24,2 moz/gal		<=22000 mg/l; <=2664 moz/gal
Salinity	n. d.		n. d.		<= 4%; <= 40.000 ppm
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal		< 50 mg/l; < 6,06 moz/gal		< 250mg/l; < 30,28 moz/gal
Temperature	4 -35° C; 39 - 95 ° F		4 -30° C; 39 - 86 ° F		4 - 20 ° C; 39 - 68 ° F
Supply and delivery according to manufacturer specifications.					
Product / proof of delivery: Schaumsprudler 75 - 20 silver Art. 50768					
OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800					
(or equivalent)					
..... Entered by the bidder					