

01 Specs 01Title	Comet 15 - 17 T			01.09.16 AO VS.02	Project No.																																				
Item / No.	Description / Quantity / Unit			Unit price	Total price																																				
01.1 Position	<p><b>Description:</b> Clear stream single jet nozzle made of brass.</p> <p>Installation and operation in freshwater.*</p> <p><b>Technical data:</b>  Dimensions (Ø x H): 63,3 x 152 [mm]  Material: brass  Weight: 0,86 kg  Effect height: 0,5 - 12,0 [m]  Nozzle diameter at orifice: 17 mm  Adjustable angular range: 15°  Water-level independent: yes</p> <p><b>Double nipple:</b>  Material: brass  Integrated flow rectifier: yes  Connecting thread (Outside thread): G1 1/2</p> <p><b>Union nut:</b>  Material: brass  Chamfered: yes  Connecting thread (Inner thread): G1 1/2  Wrench size: AF55</p> <p>*</p> <table border="1" data-bbox="300 1108 1209 1608"> <thead> <tr> <th colspan="4" data-bbox="300 1108 1209 1137">water-quality-matrix</th> </tr> <tr> <th data-bbox="300 1137 459 1167"></th> <th data-bbox="459 1137 719 1167">Freshwater</th> <th data-bbox="719 1137 975 1167">Poolwater</th> <th data-bbox="975 1137 1209 1167">Seawater</th> </tr> </thead> <tbody> <tr> <td data-bbox="300 1167 459 1234">PH.Value</td> <td data-bbox="459 1167 719 1234">7,2 -7,6</td> <td data-bbox="719 1167 975 1234">7,2 -7,6</td> <td data-bbox="975 1167 1209 1234">8</td> </tr> <tr> <td data-bbox="300 1234 459 1301">Hardness</td> <td data-bbox="459 1234 719 1301">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="719 1234 975 1301">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="975 1234 1209 1301">20 -30 ° DH; 356 - 534 ppm CaCo3</td> </tr> <tr> <td data-bbox="300 1301 459 1361">Free Chlorine</td> <td data-bbox="459 1301 719 1361">&lt; 0,3 mg/l; &lt; 0,036 moz/gal</td> <td data-bbox="719 1301 975 1361">0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td> <td data-bbox="975 1301 1209 1361">&lt; 0,3 mg/l; &lt; 0,036 moz/gal</td> </tr> <tr> <td data-bbox="300 1361 459 1422">Chlorine concentration</td> <td data-bbox="459 1361 719 1422">&lt; 250 mg/l; &lt; 30,28 moz/gal</td> <td data-bbox="719 1361 975 1422">&lt; 200 mg/l; &lt; 24,2 moz/gal</td> <td data-bbox="975 1361 1209 1422">&lt;=22000 mg/l; &lt;=2664 moz/gal</td> </tr> <tr> <td data-bbox="300 1422 459 1482">Salinity</td> <td data-bbox="459 1422 719 1482">n. d.</td> <td data-bbox="719 1422 975 1482">n. d.</td> <td data-bbox="975 1422 1209 1482">&lt;= 4%; &lt;= 40.000 ppm</td> </tr> <tr> <td data-bbox="300 1482 459 1543">Total Dry Residue</td> <td data-bbox="459 1482 719 1543">&lt; 50 mg/l; &lt; 6,06 moz/gal</td> <td data-bbox="719 1482 975 1543">&lt; 50 mg/l; &lt; 6,06 moz/gal</td> <td data-bbox="975 1482 1209 1543">&lt; 250mg/l; &lt; 30,28 moz/gal</td> </tr> <tr> <td data-bbox="300 1543 459 1608">Temperature</td> <td data-bbox="459 1543 719 1608">4 -35° C; 39 - 95 ° F</td> <td data-bbox="719 1543 975 1608">4 -30° C; 39 - 86 ° F</td> <td data-bbox="975 1543 1209 1608">4 - 20 ° C; 39 - 68 ° F</td> </tr> </tbody> </table>			water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																									
	Freshwater	Poolwater	Seawater																																						
PH.Value	7,2 -7,6	7,2 -7,6	8																																						
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																						
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																						
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																						
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																						
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																						
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																						
<p>Supply and delivery according to manufacturer specifications.</p> <p>Product / proof of delivery:  <b>Comet 15 - 17 T</b>  <b>Art. 50970</b></p> <p>OASE GmbH  Tecklenburger Str. 161  48477 Hörstel / Germany  Phone: +49 5454 800</p> <p>(or equivalent )  .....  Entered by the bidder</p>																																									