

01 Specs 01Title	Hollow Jet Nozzle 100		06.09.16 AO VS.02	Project No.																																				
Item / No.	Description / Quantity / Unit		Unit price	Total price																																				
01.1 Position	Description: Hollow jet nozzle that creates a high and wind-stable jet with low water demand. Installation and operation in fresh- and poolwater.* Technical data: Dimensions (Ø x H): 285x750 [mm] Material: 1.4571 (AISI 316) Weight: 33,0 kg Effect height: 20-50 [m] Nozzle diameter at orifice: 100 mm Water film thickness: 4,0 mm Integrated flow rectifier: yes Water-level independent: yes Nozzle connection: Connection type: DN150-Flange Pitch circle (Ø): 240 mm Number of holes: 8 Hole (Ø): 23 mm * <table><tr><th colspan="4">water-quality-matrix</th></tr><tr><th></th><th>Freshwater</th><th>Poolwater</th><th>Seawater</th></tr><tr><td>PH.Value</td><td>7,2 -7,6</td><td>7,2 -7,6</td><td>8</td></tr><tr><td>Hardness</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>8 -15 ° DH; 142 -267 ppm CaCo3</td><td>20 -30 ° DH; 356 - 534 ppm CaCo3</td></tr><tr><td>Free Chlorine</td><td>< 0,3 mg/l; < 0,036 moz/gal</td><td>0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td><td>< 0,3 mg/l; < 0,036 moz/gal</td></tr><tr><td>Chlorine concentration</td><td>< 250 mg/l; < 30,28 moz/gal</td><td>< 200 mg/l; < 24,2 moz/gal</td><td><=22000 mg/l; <=2664 moz/gal</td></tr><tr><td>Salinity</td><td>n. d.</td><td>n. d.</td><td><= 4%; <= 40.000 ppm</td></tr><tr><td>Total Dry Residue</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 50 mg/l; < 6,06 moz/gal</td><td>< 250mg/l; < 30,28 moz/gal</td></tr><tr><td>Temperature</td><td>4 -35° C; 39 - 95 ° F</td><td>4 -30° C; 39 - 86 ° F</td><td>4 - 20 ° C; 39 - 68 ° F</td></tr></table>		water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
	water-quality-matrix																																							
		Freshwater	Poolwater	Seawater																																				
	PH.Value	7,2 -7,6	7,2 -7,6	8																																				
	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																				
	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																				
	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																				
	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																				
	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																				
	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																				
	Supply and delivery according to manufacturer specifications.																																							
	Product / proof of delivery: Hollow Jet Nozzle 100 Art. 50973 OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800 (or equivalent) Entered by the bidder																																							