

01 Specs 01Title	Schaumsprudler 35-10 E			05.09.16 KF VS.01	Project No.
Item / No.	Description / Quantity / Unit			Unit Price	Total
01.1 Position	<p>OASE Description: Water-level independent stainless steel nozzle to create a homogenous and stable foam/frothy jet.</p> <p>Installation and operation in fresh-, poolwater.*</p> <p>Technical data: Dimensions (ØxH): 60x160 [mm] Material: Stainless steel 1,4301 (AISI 304) Weight: 0.5 kg Connecting thread: G1 (OT) Effect height: 0,25-2,5 [m] Nozzle orifice diameter: approx. 32 mm Integrated flow rectifier: yes Water-level independent: yes</p> <p>*</p>				
OASE water-quality-matrix					
	Freshwater	Poolwater	Seawater		
PH.Value	7,2 -7,6	7,2 -7,6	8		
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3		
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal		
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal		
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm		
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal		
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
Supply and delivery according to manufacturer specifications					
Product / proof of delivery:					
Art. 50984					
OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Fax: +49 5454 800					
(or equivalent)					
.....					
Entered by the bidder					