

01 Specs 01Title	Finger Jet 7 - 15 E			06.09.16 KF VS.02	Project No.																																				
Item / No.	Description / Quantity / Unit			Unit price	Total price																																				
01.1 Position	<p>Description: Water level independent stainless steel nozzle to create a fan like a set of 7 clear stream jets.</p> <p>Installation and operation in fresh-, pool- and seawater.*</p> <p>Technical data: Dimensions (L x W x H): 167x166x50 [mm] Material: Stainless steel 1.4404 (AISI 316L) Weight: 1.6 kg Connecting thread (Outside thread): 1 1/2 Zoll Effect height: 1.0-4.0 [m] Effect width: 2.7-7.4 [m] Number of nozzles: 7 Nozzle diameter at orifice: 10 mm Water-level independent: yes</p> <p>*</p> <table border="1" data-bbox="300 913 1236 1417"> <thead> <tr> <th colspan="4" data-bbox="300 913 1236 943">water-quality-matrix</th> </tr> <tr> <th data-bbox="300 943 464 972"></th> <th data-bbox="464 943 730 972">Freshwater</th> <th data-bbox="730 943 997 972">Poolwater</th> <th data-bbox="997 943 1236 972">Seawater</th> </tr> </thead> <tbody> <tr> <td data-bbox="300 972 464 1046">PH.Value</td> <td data-bbox="464 972 730 1046">7,2 -7,6</td> <td data-bbox="730 972 997 1046">7,2 -7,6</td> <td data-bbox="997 972 1236 1046">8</td> </tr> <tr> <td data-bbox="300 1046 464 1120">Hardness</td> <td data-bbox="464 1046 730 1120">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="730 1046 997 1120">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="997 1046 1236 1120">20 -30 ° DH; 356 - 534 ppm CaCo3</td> </tr> <tr> <td data-bbox="300 1120 464 1171">Free Chlorine</td> <td data-bbox="464 1120 730 1171">< 0,3 mg/l; < 0,036 moz/gal</td> <td data-bbox="730 1120 997 1171">0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td> <td data-bbox="997 1120 1236 1171">< 0,3 mg/l; < 0,036 moz/gal</td> </tr> <tr> <td data-bbox="300 1171 464 1245">Chlorine concentration</td> <td data-bbox="464 1171 730 1245">< 250 mg/l; < 30,28 moz/gal</td> <td data-bbox="730 1171 997 1245">< 200 mg/l; < 24,2 moz/gal</td> <td data-bbox="997 1171 1236 1245"><=22000 mg/l; <=2664 moz/gal</td> </tr> <tr> <td data-bbox="300 1245 464 1296">Salinity</td> <td data-bbox="464 1245 730 1296">n. d.</td> <td data-bbox="730 1245 997 1296">n. d.</td> <td data-bbox="997 1245 1236 1296"><= 4%; <= 40.000 ppm</td> </tr> <tr> <td data-bbox="300 1296 464 1348">Total Dry Residue</td> <td data-bbox="464 1296 730 1348">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="730 1296 997 1348">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="997 1296 1236 1348">< 250mg/l; < 30,28 moz/gal</td> </tr> <tr> <td data-bbox="300 1348 464 1417">Temperature</td> <td data-bbox="464 1348 730 1417">4 -35° C; 39 - 95 ° F</td> <td data-bbox="730 1348 997 1417">4 -30° C; 39 - 86 ° F</td> <td data-bbox="997 1348 1236 1417">4 - 20 ° C; 39 - 68 ° F</td> </tr> </tbody> </table>			water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																									
	Freshwater	Poolwater	Seawater																																						
PH.Value	7,2 -7,6	7,2 -7,6	8																																						
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																						
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																						
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																						
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																						
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																						
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																						
<p>Supply and delivery according to manufacturer specifications.</p> <p>Product / proof of delivery: Finger Jet 7 - 15 E Art. 51110</p> <p>OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800</p> <p>(or equivalent) Entered by the bidder</p>																																									