

01 Specs 01Titel	SPA 58-23	20.03.17 KF VS.01	Project No.
Item / No.	Description/ Quantity/ Unit	Unit price	Total price
01.1 Position	<p><b>Description:</b>  <b>Submersible pump, suitable for clean water. Can be installed vertically or horizontally. The pump is fitted with sand shield, lip seal, water-lubricated journal bearings and a volume compensating diaphragm. The motor is a canned type submersible motor offering good mechanical stability and high efficiency.</b></p> <p>Suitable for wet assembly.</p> <p><b>Environmental conditions for wet application (waterquality):</b>  Installation and operation in fresh-, pool- and seawater.*</p> <p><b>Technical data:</b></p> <p>Weight: 31 Kg  Dimensions (Lx W x H): 970x255x229 [mm]  incl. Filter  Speed for pump data: 2900 1/min  Rated flow: 46 m<sup>3</sup>/h  Rated head: 17 m  Approvals on nameplate: CE,EAC  Curve tolerance: ISO9906:2012 3B  Motor version: T40</p> <p><b>Materials:</b></p> <p>Pump: Stainless steel /EN 1.4301/ AISI 304  Impeller: Stainless steel /EN 1.4301/ AISI 304  Motor: Stainless steel /EN 1.4301/ AISI 304  Shaft seal for motor: HM/CER</p> <p><b>Installation:</b></p> <p>Pump outlet (Inside thread): RP3</p> <p><b>Electrical data:</b></p> <p>Motor type: MS4000  Rated power - P2: 3 kW  Power (P2) required by pump: 3 kW  Mains frequency: 50 Hz  Rated voltage: 3 x 400 V  Rated current: 7.85 A  Starting current: 4,9  Cos phi- power factor: 0.77  Rated speed: 2865 1/min  Start method: Direct online  Enclosure class (IEC 34-5): IP68  Insulation class(IEC 85): F</p>		

01 Specs 01Titel	<b>SPA 58-23</b>			20.03.17 KF VS.01	Project No.	
Item / No.	Description/ Quantity/ Unit			Unit price	Total price	
	*					
	<b>water-quality-matrix</b>					
		<b>Freshwater</b>	<b>Poolwater</b>	<b>Seawater</b>		
	PH.Value	7,2 -7,6	7,2 -7,6	8		
	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3		
	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal		
	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal		
	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm		
	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal		
	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
	Supply and delivery according to manufacturer specifications.					
	Product / proof of delivery:					
	<b>SPA 58-23</b>					
<b>Art. 53845</b>						
OASE GmbH						
Tecklenburger Str. 161						
48477 Hörstel / Germany						
Phone: +49 5454 800						
(or equivalent)						
.....						
Entered by the bidder						