

01 Specs 01Title	VarioJet 55 - 20			08.09.16 AO VS.02	Project No.																																				
Item / No.	Description / Quantity / Unit			Unit price	total price																																				
01.1 Position	<p>Description: Stainless steel water nozzle, able to create a dynamic variable water pattern, from lava- over calyx- to high jet, controlled by the flow-rate variations of two independent pumps (not included).</p> <p>Installation and operation in fresh- and poolwater.*</p> <p>Technical data: Dimensions (Ø x H): 150 x 883 [mm] Material: Stainless steel 1.4301 (AISI 304) Weight: 13,2 kg Connecting thread (laterally, Outside thread): G2 Connecting thread (bottom, Inner thread): G2 Adjusting flange: yes moving parts subject to wear: none Able to mount directly on pump: yes</p> <p>*</p> <table border="1" data-bbox="295 952 1225 1478"> <thead> <tr> <th colspan="4" data-bbox="295 952 1225 985">water-quality-matrix</th> </tr> <tr> <th data-bbox="295 985 459 1019"></th> <th data-bbox="459 985 730 1019">Freshwater</th> <th data-bbox="730 985 986 1019">Poolwater</th> <th data-bbox="986 985 1225 1019">Seawater</th> </tr> </thead> <tbody> <tr> <td data-bbox="295 1019 459 1064">PH.Value</td> <td data-bbox="459 1019 730 1064">7,2 -7,6</td> <td data-bbox="730 1019 986 1064">7,2 -7,6</td> <td data-bbox="986 1019 1225 1064">8</td> </tr> <tr> <td data-bbox="295 1064 459 1131">Hardness</td> <td data-bbox="459 1064 730 1131">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="730 1064 986 1131">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="986 1064 1225 1131">20 -30 ° DH; 356 - 534 ppm CaCo3</td> </tr> <tr> <td data-bbox="295 1131 459 1198">Free Chlorine</td> <td data-bbox="459 1131 730 1198">< 0,3 mg/l; < 0,036 moz/gal</td> <td data-bbox="730 1131 986 1198">0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td> <td data-bbox="986 1131 1225 1198">< 0,3 mg/l; < 0,036 moz/gal</td> </tr> <tr> <td data-bbox="295 1198 459 1265">Chlorine concentration</td> <td data-bbox="459 1198 730 1265">< 250 mg/l; < 30,28 moz/gal</td> <td data-bbox="730 1198 986 1265">< 200 mg/l; < 24,2 moz/gal</td> <td data-bbox="986 1198 1225 1265"><=22000 mg/l; <=2664 moz/gal</td> </tr> <tr> <td data-bbox="295 1265 459 1332">Salinity</td> <td data-bbox="459 1265 730 1332">n. d.</td> <td data-bbox="730 1265 986 1332">n. d.</td> <td data-bbox="986 1265 1225 1332"><= 4%; <= 40.000 ppm</td> </tr> <tr> <td data-bbox="295 1332 459 1411">Total Dry Residue</td> <td data-bbox="459 1332 730 1411">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="730 1332 986 1411">< 50 mg/l; < 6,06 moz/gal</td> <td data-bbox="986 1332 1225 1411">< 250mg/l; < 30,28 moz/gal</td> </tr> <tr> <td data-bbox="295 1411 459 1478">Temperature</td> <td data-bbox="459 1411 730 1478">4 -35° C; 39 - 95 ° F</td> <td data-bbox="730 1411 986 1478">4 -30° C; 39 - 86 ° F</td> <td data-bbox="986 1411 1225 1478">4 - 20 ° C; 39 - 68 ° F</td> </tr> </tbody> </table> <p>Supply and delivery according to manufacturer specifications.</p> <p>Product / proof of delivery: VarioJet 55 - 20 Art. 58906 B</p> <p>OASE GmbH Tecklenburger Str. 161 48477 Hörstel / Germany Phone: +49 5454 800</p> <p>(or equivalent) Entered by the bidder</p>			water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																									
	Freshwater	Poolwater	Seawater																																						
PH.Value	7,2 -7,6	7,2 -7,6	8																																						
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																						
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																						
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																						
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																						
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																						
Temperature	4 -35° C; 39 - 95 ° F	4 -30° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																						