

01 Specs 01Title	QuickFix MDD L			06.09.16 AO VS.02	Project No.																																				
Item / No.	Description / Quantity / Unit			Unit price	Total price																																				
01.1 Position	<p><b>Description:</b>  <b>Made of stainless steel / plastic - POM quick mounting device for Multidirectional Drive L 2D</b>  .....  Installation and operation in fresh-, pool- and seawater.*</p> <p><b>Technical data:</b>  Dimensions (L X W x H): 175x625x43.5 [mm]  Material: Stainless steel/Plastic-POM  Weight: 3.4  Number of holes: 2  Hole (∅): 13 mm</p> <p>*</p> <table border="1" data-bbox="296 974 1209 1473"> <thead> <tr> <th colspan="4" data-bbox="296 974 1209 1003">water-quality-matrix</th> </tr> <tr> <th data-bbox="296 1003 459 1032"></th> <th data-bbox="459 1003 718 1032">Freshwater</th> <th data-bbox="718 1003 975 1032">Poolwater</th> <th data-bbox="975 1003 1209 1032">Seawater</th> </tr> </thead> <tbody> <tr> <td data-bbox="296 1032 459 1099">PH.Value</td> <td data-bbox="459 1032 718 1099">7,2 -7,6</td> <td data-bbox="718 1032 975 1099">7,2 -7,6</td> <td data-bbox="975 1032 1209 1099">8</td> </tr> <tr> <td data-bbox="296 1099 459 1167">Hardness</td> <td data-bbox="459 1099 718 1167">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="718 1099 975 1167">8 -15 ° DH; 142 -267 ppm CaCo3</td> <td data-bbox="975 1099 1209 1167">20 -30 ° DH; 356 - 534 ppm CaCo3</td> </tr> <tr> <td data-bbox="296 1167 459 1223">Free Chlorine</td> <td data-bbox="459 1167 718 1223">&lt; 0,3 mg/l; &lt; 0,036 moz/gal</td> <td data-bbox="718 1167 975 1223">0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal</td> <td data-bbox="975 1167 1209 1223">&lt; 0,3 mg/l; &lt; 0,036 moz/gal</td> </tr> <tr> <td data-bbox="296 1223 459 1290">Chlorine concentration</td> <td data-bbox="459 1223 718 1290">&lt; 250 mg/l; &lt; 30,28 moz/gal</td> <td data-bbox="718 1223 975 1290">&lt; 200 mg/l; &lt; 24,2 moz/gal</td> <td data-bbox="975 1223 1209 1290">&lt;=22000 mg/l; &lt;=2664 moz/gal</td> </tr> <tr> <td data-bbox="296 1290 459 1346">Salinity</td> <td data-bbox="459 1290 718 1346">n. d.</td> <td data-bbox="718 1290 975 1346">n. d.</td> <td data-bbox="975 1290 1209 1346">&lt;= 4%; &lt;= 40.000 ppm</td> </tr> <tr> <td data-bbox="296 1346 459 1413">Total Dry Residue</td> <td data-bbox="459 1346 718 1413">&lt; 50 mg/l; &lt; 6,06 moz/gal</td> <td data-bbox="718 1346 975 1413">&lt; 50 mg/l; &lt; 6,06 moz/gal</td> <td data-bbox="975 1346 1209 1413">&lt; 250mg/l; &lt; 30,28 moz/gal</td> </tr> <tr> <td data-bbox="296 1413 459 1473">Temperature</td> <td data-bbox="459 1413 718 1473">4 -35 ° C; 39 - 95 ° F</td> <td data-bbox="718 1413 975 1473">4 -30 ° C; 39 - 86 ° F</td> <td data-bbox="975 1413 1209 1473">4 - 20 ° C; 39 - 68 ° F</td> </tr> </tbody> </table> <p>Supply and delivery according to manufacturer specifications.</p> <p>Product / proof of delivery:  <b>QuickFix MDD L</b>  <b>Art. 70430</b></p> <p>OASE GmbH  Tecklenburger Str. 161  48477 Hörstel / Germany  Phone: +49 5454 800</p> <p>(or equivalent )  .....  Entered by the bidder</p>			water-quality-matrix					Freshwater	Poolwater	Seawater	PH.Value	7,2 -7,6	7,2 -7,6	8	Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3	Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal	Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal	Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm	Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal	Temperature	4 -35 ° C; 39 - 95 ° F	4 -30 ° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F		
water-quality-matrix																																									
	Freshwater	Poolwater	Seawater																																						
PH.Value	7,2 -7,6	7,2 -7,6	8																																						
Hardness	8 -15 ° DH; 142 -267 ppm CaCo3	8 -15 ° DH; 142 -267 ppm CaCo3	20 -30 ° DH; 356 - 534 ppm CaCo3																																						
Free Chlorine	< 0,3 mg/l; < 0,036 moz/gal	0,3 -0,6 mg/l; 0,036 - 0,072 moz/gal	< 0,3 mg/l; < 0,036 moz/gal																																						
Chlorine concentration	< 250 mg/l; < 30,28 moz/gal	< 200 mg/l; < 24,2 moz/gal	<=22000 mg/l; <=2664 moz/gal																																						
Salinity	n. d.	n. d.	<= 4%; <= 40.000 ppm																																						
Total Dry Residue	< 50 mg/l; < 6,06 moz/gal	< 50 mg/l; < 6,06 moz/gal	< 250mg/l; < 30,28 moz/gal																																						
Temperature	4 -35 ° C; 39 - 95 ° F	4 -30 ° C; 39 - 86 ° F	4 - 20 ° C; 39 - 68 ° F																																						